

TO-252 .> // x N ?ú 3 MOS « | • 'ož

N-CHANNEL MOSFET in a TO-252 Plastic Package.

z õ > z F Ø • ¼ , † ½ —)í D }ož

Low gate charge, low crss, fast switching, HF Product. Have good Electromagnetic Interference performance, HF Product.

¥ ~ ^ 9 F ~ y - ~ ä • ¼ èož

These devices are well suited for power switch circuit of adaptor and charger.

PIN1 y G

PIN 2 y D

PIN 3 y

Ô ? d • Ž ¢ / Electrical Characteristic Curve

Ø □ =) ¢ / Package Dimensions

BR
4N80

^a ¢ y
BR y , [W A
4 y ° Z W A
y Ÿ D Z W A k Š Ÿ D Z J

Note:


BR: Company Code

4N80: Product Type Code

*****: Lot No. Code, code change with Lot No

šWD t...•Žč (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

7HPSHUDWXUH



7LPH VHF

a č y

10• Ä ½ “† 150 ½180 - k ž • 60 ½90sec;

20• Q > “† 245 r5 - k ž • 4 Ò 5 r0.5sec;

30•D N ò i Ò 0 ,† 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Că p ¯ »] / Resistance to Soldering Heat Test Conditions

“† y 260 r5 -

ž • y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
TO-252	2,500	2	5,000	6	30,000	13 s ×16	360×360×50	380×335×366

ì' x / TUBE

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Tube /•1×	Tubes/Inner Box •1× /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Tube•1×	Inner Box	Outer Boxç
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

„Đ y f / Notices